

 TECHNICAL SPECIFICATIONS (METRIC)												
Region spec	Duration	Air capacity	Service pressure	Diameter	Length	Weight	Water volume	Thread size	Service life	Material	Part number	Product family
	<i>Min</i>	<i>l</i>	<i>bar</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>l</i>		<i>years</i>			
USA	30	1274	379	127	462	2.6	3.8	M18 x 1.5	15	Full wrap carbon	L46A	HP
USA	30	1274	310	138	460	2.7	4.6	0.875-14UNF	15	Full wrap carbon	L45R	SL
USA	30	1274	310	138	467	3.0	4.6	0.875-14UNF	15	Full wrap carbon	L45M-XD	XD
USA	30	1274	310	140	474	3.2	4.6	0.875-14UNF	30	Full wrap carbon	L45Z	EL
USA	30	1274	153	167	519	3.2	8.5	0.750-16UNF	15	Full wrap carbon	L45G	LCX
USA	30	1274	310	138	467	3.0	4.6	0.875-14UNF	15	Full wrap carbon	L45M	LCX
USA	30	1274	153	172	488	3.1	8.4	0.750-16UNF	15	Full wrap carbon	L45S	LCX
USA	30	1274	153	171	530	7.1	8.4	0.750-16UNF-2B, 1.125-12UNF-2B	NLL	Aluminum	L045	L6X-AL
-	-	-	-	-	-	-	-	-	-	-	-	-
USA	45	1840	379	148	501	3.6	5.7	M18 x 1.5	15	Full wrap carbon	L66D	HP
USA	45	1840	310	160	508	3.6	6.8	0.875-14UNF	15	Full wrap carbon	L65R	SL
USA	45	1840	310	173	452	3.8	6.8	0.875-14UNF	15	Full wrap carbon	L66B	SL
USA	45	1840	310	159	516	4.1	6.8	0.875-14UNF	15	Full wrap carbon	L65G-XD	XD
USA	45	1840	310	163	525	4.5	6.8	0.875-14UNF	30	Full wrap carbon	L65Z	EL
USA	45	1698	207	172	526	4.2	8.5	0.750-16UNF	15	Full wrap carbon	L62M	LCX
USA	45	1840	310	159	516	4.1	6.8	0.875-14UNF	15	Full wrap carbon	L65G	LCX
USA	45	1840	310	172	457	4.2	6.8	0.875-14	15	Full wrap carbon	L65M	LCX
USA	-	-	-	-	-	-	-	-	-	-	-	-
USA	60	2462	379	171	506	4.6	7.6	M18 x 1.5	15	Full wrap carbon	L87V	HP
USA	60	2462	310	181	530	4.9	9.0	0.875-14UNF	15	Full wrap carbon	L87E	SL
USA	60	2462	310	175	541	4.6	9.0	0.875-14UNF	15	Full wrap carbon	L87R	SL
USA	60	2462	310	175	550	5.3	9.0	0.875-14UNF	15	Full wrap carbon	L87G-XD	XD
USA	60	2462	310	178	550	5.9	9.0	0.875-14UNF	30	Full wrap carbon	L87Z	EL
USA	60	2462	310	175	551	5.3	9.0	0.875-14UNF	15	Full wrap carbon	L87C	LCX
USA	60	2462	310	175	550	5.3	9.0	0.875-14UNF	15	Full wrap carbon	L87G	LCX
USA	60	2462	310	181	531	5.3	9.0	0.875-14UNF	15	Full wrap carbon	L87M	LCX

Region spec	Duration	Air capacity	Service pressure	Diameter	Length	Weight	Water volume	Thread size	Service life	Material	Part number	Product family
-	-	-	-	-	-	-	-	-	-	-	-	-
USA	75	3113	379	180	562	5.8	9.5	M18 x 1.5	15	Full wrap carbon	L110C	HP
-	-	-	-	-	-	-	-	-	-	-	-	-
Europe	-	1132	300	117	580	2.7	4.2	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L43F	LCX-15Y
Europe	-	1132	300	120	582	2.9	4.2	M18 x 1.5 CLASS 6H	30	L6X - Full-wrap carbon	L43G	LCX-30Y
Europe	-	1274	300	137	480	2.8	4.7	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L45X	LCX-15Y
Europe	-	1623	300	156	470	3.4	6.0	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L58F	LCX-15Y
Europe	-	1623	300	160	463	3.7	6.0	M18 x 1.5 CLASS 6H	30	L6X - Full-wrap carbon	L58G	LCX-30Y
Europe	-	1641	300	151	526	6.0	6.0	M18 x 1.5 CLASS 6H	NLL	L7X Hoop-wrap	BFK145	L7X-HW
Europe	-	1840	300	157	530	4.2	6.8	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L65N	LCX-15Y
Europe	-	1840	300	158	521	3.7	6.8	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L66F	LCX-15Y
Europe	-	1840	300	161	523	4.0	6.8	M18 x 1.5 CLASS 6H	20	L6X - Full-wrap carbon	L65E	LCX-20Y
Europe	-	1840	300	163	525	4.4	6.8	M18 x 1.5 CLASS 6H	30	L6X - Full-wrap carbon	L65B	LCX-30Y
Europe	-	2434	300	173	556	4.8	9.0	M18 x 1.5 CLASS 6H	15	L6X - Full-wrap carbon	L87A	LCX-15Y
Europe	-	2434	300	178	550	5.9	9.0	M18 x 1.5 CLASS 6H	30	L6X - Full-wrap carbon	L87A	LCX-30Y

 INFO

 TECHNICAL SPECIFICATIONS (IMPERIAL)

 INFO